



注：L 随整机长度而定，但最长不得超过4米。

⑪	GB93-87	弹垫 10	2																		
⑩	GB97.2-85	平垫 10	2																		
⑨	GB5782-86	螺栓M10x45	2																		
⑧	GB93-87	弹垫 16	3																		
⑦	GB97.2-85	平垫 16	3																		
⑥	GB5782-86	螺栓M16x35	2																		
⑤	GB93-87	弹垫 10	6																		
④	GB97.2-85	平垫 10	6																		
③	GB5780-86	螺栓M10x30	6																		
②	YF07.3	直角管接头M10x1	1																		
①	YF05.3	铜管接头M10x1	1																		
16	LSY180-221	轴承压盖	1	ZG270~500																	
15	LSY180-223	尼龙护套	2	尼龙																	
14	LSY180-219	观察孔连接法兰	1	Q235																	

13	LSY180-217	观察孔盖	1	Q235																	
12	LSY180-218	连接管φ194x6	1	20																	
11	LSY180-211	吊耳	2	Q235																	
10	LSY180-210	大叶片		16Mn																	
9	LSY180-302	芯管	1	20																	
8	LSY180-208	花键轴堵	2	Q235																	
7	LSY180-207	内花键套	2	40Cr																	
6	LSY180-206	中心花键轴	1	40Cr																	
5	LSY180-205	吊座滑动轴承	1	锌基合金																	
4	LSY180-204	轴承吊座	1	ZG270~500																	
3	LSY180-203	过油螺栓	1	45																	
2	LSY180-301	无缝钢管	1	20																	
1	LSY180-201	管体连接法兰	2	Q235																	

序号	代号	名称	数量	材料	单件重量	总计重量	备注
							第二部分传动部装
							LSY180-300
标记	处数	更改文件号	签名	日期	阶段标记	重量	比例
设计	李连通		工艺				
校对	秦海波		标准				
审核	刘飞		批准				
							共 张 第 张

